

MARK3-53 CAT ETCHER

Hand-Held - Wireless - Rugged



From Insta Etch
confirm upon unboxing


- 1x Wireless Hand Marker w/ Adjustable High Heat Marking Head
- 2x 3.0 Ah Makita Batteries - 3 hour continuous use, all-day intermittent use - Li-Ion
- 1x Makita Smart Battery Charger
- 1x (Optional) - Samsung 8" drop protection enterprise tablet - Android System USB-C

Mark3-53 Cat Etcher APP UPDATE

This easy process will install the updated Insta Etch Mark3 Cat Etcher app into your Tablet.

MOVE TO TECHNICIAN QUICK START Guide Page3 if COMPLETE.

- 1) Find the **Red "M3Marker"** App Long-Press (Press your finger and hold) on the app icon and **"UNINSTALL"**



- 2) Now go to Android Settings ... its the gear icon app



Click Connections - Wi-Fi
Connect to any internet wi-fi available.

continued


Mark3-53 Cat Etcher APP UPDATE

[CLICK THIS LINK TO DOWNLOAD APP](https://www.instaetch.com/ota.php) OR Type URL on Tablet Internet App (Chrome Icon):


<https://www.instaetch.com/ota.php>

3) Download "CAT ETCH SOFTWARE" and Install

It may automatically ask you to "Install" to update.



3a




3b

OR you may have to find the newly downloaded file to install. **Find SAMSUNG APP folder > My Files > Installation Files (APK)**

4) Go back to Android Settings ... its the gear icon app



Then: **Connections > Forget** (Your new internet connection)



continued

MARK3-53 CAT MARKER

Hand-Held - Wireless - Rugged



Vehicle Marking Systems

1-888-804-5475

+1-602-481-9444

info@instaEtch.com

Mark3-53 Cat Etcher Setup


1) **Press & Hold Trigger To Begin the Tablet Pairing.**

Release trigger when **Green light illuminates.**

This opens it's own wi-fi signal for tablet to auto-connect when both are on. *Do Not connect tablet to your building's internet.*



1st Time Users Go To Wi-Fi



2)

Now go to IE application  on your Tablet...



Recommended Settings
1st Change Units to be Inches: OFF
Select Font - 11x16 DOT.dot (optional)
Font Height: 5.5mm Spacing in Char: .60mm
Width Scale: 60% DataMatrix: 10mm
Logo Hgt: 10mm Distance Blocks: 1.5mm
Force Code: 7 Adjust Artboard Width : OFF
Max Letters: 17 Extract Last Letters: ON
Letters to Extract: 17 Units Inches: OFF
AutoConnect: OFF Marking 1 Time: OFF
Wait at 1st Point: OFF Record Report: OFF

Tech Line: 480-545-6614

Insta Mark3-53 App Advanced Features

How-To Scan a Barcode: **Scan Barcode**



The barcode scanner will automatically generate & actively auto focus/capture. Make sure complete barcode is centered in scan screen.

How-To Extract & Validate correct VIN



Make sure Extraction is on & set to 17 digits.



Battery=74%

10ERRFFG4NN251139

Connexec

Enter the 17 Marking Strings:

10ERRFFG4NN251139

Render to Antboard

Send to Marker

Scan Barcode

Convert to Datamatrix

Remove Second Entity

10ERRFFG4NN251139

A valid hand-typed or scanned VIN will appear **green!!**

How-To Mark a QRcode: Convert to DataMatrix

Some CATs may be more tucked into the frame of the vehicle, which makes it difficult to steal, but also more difficult to mark. Center the marker in contact with CAT, and use this VIN encoded format to mark traceable “QR” code.

Simply Type or Scan and “Render to Artboard”, then tap - Convert to Datamatrix, finally “Send to Marker”

How-To Mark additional Art:



You may add an additional text line or
Advanced users may add a LOGO .PLT file to the artboard.



The screenshot shows the application interface. On the left is a vertical toolbar with icons for home, Wi-Fi, search, settings, hammer & wrench, and a document. The main area displays a 'STOP' sign logo and a green VIN '10ERRYPG4NN251'. Below the VIN, it says 'Not Connected...'. On the right, a panel titled 'Enter the 1 Marking Strings:' shows 'MARKING STRING 1' and a list of buttons: 'Render to Artboard', 'Send to Marker', 'Scan Barcode', 'Convert to Datamatrix', and 'Remove Second Entry'.

First click the Hammer & Wrench Icon, and add.
NOTE: You may not change entered additional line text as this new line is static. For LOGOS or art, view existing .PLT files or advanced users add their own.

FINAL PREP & PRECAUTIONS



**MARK3-53
Hand-Held
Cat Marker**



**Make Sure Cat
Converter Is @ Safe
Temp to handle!**

**USE HIGH TEMP Protective Gloves
DO NOT TOUCH CAT!**



**Secure Lifted Vehicle
w/ Blocks / Parking Brake
TURN OFF VEHICLE**



7)



**Apply Marker flat to part
and hold firmly in place.
For smaller or odd parts,
adjust wing-nuts on head
so marking pin tip is a few
mm from Cat part surface.
Press Trigger Once to align
pin to starting point, & a 2nd
trigger pull to begin marking!**

**Must Confirm correct VIN / Scan Prior to Marking.
DO NOT Mark while exhaust is HOT or car unsecured.
Spray or wipe w/ H2O to clean or cool Cat.**

**Use of this kit indicates knowledge & acceptance of instructions and safety rules.
No liability is assumed by Maximus Auto Group for incorrect use or unsatisfactory etch/markings.**

MARK3-53 CAT MARKER Hand-Held - Wireless - Rugged




Vehicle Marking Systems
1-888-804-5475
+1-602-481-9444
info@instaetch.com

Mark3-53 Cat Etcher Setup

- 1) Press & Hold Trigger To Begin the Tablet Pairing. Release trigger when Green light illuminates. This opens it's own wi-fi signal for Tablet to auto-connect when both are on. Do Not connect tablet to your building's internet.



1st Time Users Go To Wi-Fi



2) Now go to IE application on your Tablet

- Recommended Settings**
- 1st Change: Units to be Inches: OFF
 - Select Font: - 11x16 DOT (dot optional)
 - Font Height: 55mm Spacing in Char: 60mm
 - Width Scale: 60%
 - DataMatrix: #10mm
 - Logo Hgt: 10mm
 - Distance Blocks: 1.5mm
 - Force Code: 7 Adjust Artboard Width: OFF
 - Max Letters: 17 Extract Last Letters: ON
 - Letters to Extract: 17 Units Inches: OFF
 - AutoConnect: OFF Marking 1 Time: OFF
 - Wait at 1st Point: OFF Record Report: OFF

Tech Line: 490-545-6614

How-To Mark a QRcode: Convert to DataMatrix

Some CATs may be more tucked into the frame of the vehicle, which makes it difficult to steal, but also more difficult to mark. Center the marker in contact with CAT, and use this VIN encoded format to mark traceable "QR" code. Simply Type or Scan and "Render to Artboard", then tap - Convert to DataMatrix, finally "Send to Marker"

How-To Mark additional Art

You may add an additional text line or Advanced users may add a LOGO .PLT file to the artboard.



First click the Hammer & Wrench icon, and add. NOTE: You may not change entered additional line text as this new line is static. For LOGOS or art, view existing .PLT files or advanced users add their own.

3) Complete the Mark3 & Tablet Connection

Press Wi-Fi Button on screen. The Wi-Fi icon will turn Dark Blue upon connection.

4) Optional Adjust Settings



The FINAL step is ALWAYS Make sure to SEND TO MARKER- it will flash w/ Success!

FINAL PREP & PRECAUTIONS

- MARK3-53 Hand-Held Cat Marker
- Make Sure Cat Converter is @ Safe Temp to handle!
- USE HIGH TEMP Protective Gloves
- Secure Lifted Vehicle w/ Blocks/ Parking Brake TURN OFF VEHICLE



Apply Marker flat to part and hold firmly in place. For smaller or odd parts, adjust wing-nuts on head so marking pin tip is a few mm from Cat part surface. Press Trigger. Once to align pin to starting point, & 2nd trigger pull to begin marking!

Must Confirm correct VIN/ Scan Prior to Marking. DO NOT Mark while exhaust is HOT or car unsecured. Spray or wipe w/ H2O to clean or cool Cat.

Use of this kit indicates knowledge & acceptance of instructions and safety rules. No liability is assumed by Hammer Auto Group for incorrect use or unsatisfactory etchmarking.


How-To Scan a Barcode: Scan Barcode



The barcode scanner will automatically generate & actively auto focus/capture. Make sure complete barcode is centered in scan screen.

How-To Extract & Validate correct VIN

Make sure Extraction is on & set to T7 digits.



A valid hand-typed or scanned VIN will appear green!!